

EXTRA - FLEX

ELASTOMERIC

MASONRY PAINT



STRETCHES UP TO 400%

*BRUSH *ROLLER *SPRAY *WATER BASED *QUICK DRYING
COLOUR AVAILABILITY

- | | | | | |
|------------|-----------|----------------|------------|--------------|
| OLD WHITE | GARDENIA | CREAM | MAGNOLIA | SUFFOLK PINK |
| BUTTERMILK | PARCHMENT | PORTLAND STONE | SAND STONE | BLACK |

ALSO AVAILABLE IN **BRILLIANT WHITE**



EXTRA - FLEX ELASTOMERIC MASONRY PAINT

Bedec Extra-Flex Masonry paint is ideally suited for the protection of exterior masonry, roughcast, pebble-dash, brickwork, cement and concrete rendered surfaces.

It can be applied to previously painted surfaces after suitable preparation. This modified acrylic blend is a flexible microporous protective coating that will flex with the substrate where movement causes cracking in conventional masonry paint.

Directions for use

Stir thoroughly, check colour before use. Apply by brush roller or spray (use HVLP or Airless spray for best results). Do not apply at temperatures below 10° Centigrade or when foggy or likely to rain before the paint has dried. Ensure all surfaces are free from oil, grease, dirt, dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper.

Areas affected by mould, lichen, algae or moss should be treated with a suitable fungicidal wash.

On untreated, new cement, render etc. or any porous substrate the first coat should be thinned with approx. 30% clean water. Then apply at least two full coats for maximum protection.

Coverage

5 litres will cover approx. 50 square metres per coat depending upon substrate texture, porosity and application method.

Drying

Touch dry 2 hours, recoatable after 4 hours at 18°C 65% relative humidity.

Clean up

Clean tools and equipment with water immediately after use.

Wise Precautions

Ensure good ventilation during application and drying.

Avoid contact with skin and eyes.

When applying it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash off immediately with soap and water or a recognised skin cleanser.

Do not use solvent, thinners or white spirit.

Keep out of reach of children.

In case of insufficient ventilation during spraying wear suitable respiratory equipment.

Do not store by hanging on a hook.

Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste paint.

Avoid the inhalation of dust. Wear suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre- 1960s paint surfaces over wood and metal as they may contain harmful lead.

Do not store at low temperatures, protect from frost.

Flash Point: Not applicable.

Pack Sizes: 5 litres

Colour Range: Brilliant White, Black, Old White, Suffolk Pink, Cream, Sandstone, Portland Stone, Parchment, Buttermilk (BS10-C-31), Gardenia (BS10-B-15), Magnolia (BS08-B15). Other colours made to order subject to economical batch quantities.

VOC: EU limit for this product (cat.A/c): 75g/l (2007) / 40g/l (2010). This product contains max. 40g/l VOC

BEDEC PRODUCTS LIMITED
Units 1&2 Poplars Farm
Aythorpe Roding
Dunmow
Essex
CM6 1RY

Tel: 01279 876657
Fax: 01279 876008

www.bedec.co.uk
email: info@bedec.co.uk