



SPRAY DAY LIGHT™



BRIGHT WHITE

**FLAT MATT (2%)
ANTI-REFLECTIVE**

Water Based
High Opacity
Quick Dry
Low Flashing



Non Yellowing
Breathable
Low Odour
Wipeable

INTERIOR WALLS AND CEILINGS

TINTABLE (TO PASTEL COLOURS)

BEDEC SPRAY DAY LIGHT™

Is a high quality, minimal VOC, non yellowing, high whiteness and brightness paint with excellent covering. It gives a low matt finish (less than 2%) with low reflectivity.

Quick drying, Wipeable and Microporous with low flashing.

Formulated to coat interior ceilings and walls.

Ideal for Airless spray, HVLP Spray, Brush or Roller.

Directions for use:

Stir thoroughly, check colour before use. Apply by brush roller or spray. Do not apply at temperatures below 8°C Centigrade. Ensure all surfaces are free from oil, grease, dirt, dust and loose particles. On existing painted surfaces remove all loose and flaking paint and rub down with abrasive paper where necessary.

Areas affected by mould should be treated with a suitable fungicidal wash.

On plasterboard or any porous substrate prime the surface by applying a first coat thinned with approximately 30% clean water.

After preparation, apply at least one full coat and allow to dry. Then apply a further coat if necessary to ensure even coverage.

Airless Spray: Spray tip 15 to 17thou, pressure 2500 - 3000 psi fan width 12 inch 50 degree.

Tintable: Use compatible acrylic or universal colourants up to a maximum 6% by volume.

Coverage: 5 litres will cover approximately 50 sq metres per coat depending upon substrate texture, porosity and application method.

Drying: Touch dry 2 hours, recoatable after 4 hours at 18°C relative humidity.

Flash Point: Not applicable - water based.

Clean up: Clean tools and equipment with water immediately after use.

Wise Precautions:

Keep out of reach of children. Ensure good ventilation during application and drying.

Do not breathe spray. Wear respiratory protection. Do not get in eyes, on skin, or on clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do.

Continue rinsing. IF ON SKIN: Wash with plenty of water. Do not use solvent or thinners or white spirit.

IF SWALLOWED: Call a POISON CENTRE or doctor. If you feel unwell. If medical advice is needed have

Product container or label at hand. Dispose of contents / container to a waste disposal site in

accordance with local / national guidelines. Avoid the inhalation of dust. Wear suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre -1960s paint surfaces over wood or metal

As they may contain harmful lead.

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheets available on request.

Do not store at low temperatures, protect from frost.

Transport and store in a secure upright position. Lift with care



www.bedec.co.uk

info@bedec.co.uk

Tel: 01279876657

Bedec Products Ltd. Dunmow, Essex CM6 1RY