Surface Coating Specialists

UNITS 1 & 2, POPLARS FARM, AYTHORPE RODING, DUNMOW, ESSEX CM6 1RY
TEL: 01279 876 657 FAX: 01279 876 008 email: info@bedec.co.uk Web site www.bedec.co.uk
VAT No. GB 432114990

## ACRYLIC MULTI SURFACE VARNISH

\*Water Based
\*Low odour
\*Non Flammable

**Description:** A water based interior varnish manufactured on an acrylic resin, reinforced with Polyurethane, which does not embrittle on ageing. Available in gloss, satin or matt finishes.

**Uses:** Designed for application to most interior substrates including wood, non-ferrous metals, and most types of plastic.

**Preparation:** Surfaces must be sound, clean dry and free from wax grease and oil. Remove all dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper.

**Application:** Stir thoroughly before use. Apply by brush, roller or spray. On hardwood and porous surfaces, it is recommended that an initial well-thinned coat be applied. Ensure adequate ventilation during application and drying. Do not apply at temperatures below 8°C, or when raining or foggy.

**Coverage:** Approximately 15-20sq. metres/litre. depending on porosity and texture of the

substrate.

**Drying:** Normally 2 hours @ 18° Centigrade and 65% humidity.

**Recoatable:** After 4 hours.

Flash Point: Not applicable.

Directors: D M Horn MIScT ATSC; M B Higgins.

Clean up: Warm soapy water.

Pack sizes: 2.5 litre 1 litre 500mls

**Storage:** Keep out of reach of children. Protect from frost.

Colour Range: Clear. (Gloss, Satin and Matt)