

BEDEC

THE PAINT COMPANY

ALL PRIME[®]

ALL SURFACE ALL PURPOSE



- ALL SURFACE ALL PURPOSE WHITE PRIMER
- QUICK DRYING AND RECOATABLE AFTER 4 HOURS
- WATER-BASED AND ENVIRONMENTALLY FRIENDLY
- BOND COAT, KNOTTING, STAIN BLOCKING PRIMER AND SEALER
- USE ON WALLS, CEILINGS, DOORS, TRIM, FASCIA, SOFFITS, RAILINGS, FERROUS AND NON-FERROUS METALS
- AVAILABLE IN 750ML AND 2.5 LITRE SIZES

Innovators in Water-based Technology

Bedec Products Ltd., Units 1 & 2 Poplars Farm, Aythorpe Roding, Dunmow, Essex. CM6 1RY

Tel: +44 (0) 1279 876 657

Email: info@bedec.co.uk

www.bedec.co.uk



All surface, all purpose, bond coat, metal primer, wood primer, knotting water-based interior/ exterior stain blocking primer and sealer.

DESCRIPTION:

For interior and exterior walls, ceilings, doors, trim, fascia, soffits, foundations, railings, ferrous, non-ferrous metals and related paintable surfaces. Some stains may require a second coat. For best results, allow to dry overnight before applying topcoat. Very porous woods may require two coats before the topcoat.

SURFACE PREPARATION:

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, oil, wax, mould, wallpaper adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with a household cleaner, appropriate cleaning solution or methylated spirits and rinse off. Clean new galvanized with methylated spirits. Remove any unsound coatings. Sand any remaining paint film edges smooth and level with the new surface. New plaster which is polished or dusty should be abraded to open the surface. Lightly sand exposed wood with 80 to 100 grit sandpaper to remove loose or weathered wood fibres. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping etc. Remove mould and treat area with a fungicidal wash. Remove rust/wire brush rusty areas and wipe with methylated spirits. Spot prime knots and sap streaks after suitable preparation. Glossy surfaces - Adheres to glossy enamel paints and clear finishes, contiboard MDF, PVC, fibreglass, vinyl, ceramic wall tiles. Pre-sanding or surface deglossing may be needed.

APPLICATION:

Stir well before using. Apply when the air and surface temperature is above 5°C and relative humidity is less than 85%. Spraying – Depending upon equipment Airless Spray – 2500 psi 13 to 15 thou tip, 50° Angle, HVLP – up to 15% clean water 15 to 18 thou tip. Ready to use – no dilution necessary unless on porous surfaces where a thinned down priming coat (up to 30%) with clean water is required. TINTING: Can be tinted with up to 2% universal tinter.

DRYING TIME:

At 18°C and 65% relative humidity dry to touch in two hours, re-coatable after four hours. Topcoat within 30 days. Full adhesion and hardness develop in 7 days.

COVERAGE:

10m² per litre. Coverage may vary with surface porosity.

CLEANUP:

Clean application tools with warm water and liquid detergent. Dispose of unused or unwanted product in accordance with local laws regulating water-based coatings.

WISE PRECAUTIONS:

Keep out of reach of children. Ensure good ventilation during application and drying. Do not breathe spray. Warning, hazardous droplets may be formed when sprayed. Wear respiratory protection. Do not get in eyes, on skin or on clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing.

IF ON SKIN: Wash with plenty of water. Do not use solvent, thinners or white spirit.

IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

If medical advice is needed, have a product container or label at hand. Avoid the inhalation of dust. Wear suitable face mask if dry sanding, special precautions should be taken during surface preparation of pre - 1960s paint surfaces over wood and metal as they may contain harmful lead.

LIMITATIONS:

BEDEC – ALL PRIME® is not intended for blocking heavy water stains or for application to floors, decks, roof surfaces or any surface subject to immersion or prolonged contact with water. These limitations are not to be construed as all inclusive. Thinning may affect stain blocking properties.

WARRANTY:

BEDEC – ALL PRIME® is guaranteed to perform as indicated when applied according to label directions to a properly prepared surface. Directions are as complete as possible but cannot encompass all conditions, applications and/or surfaces beyond manufacturer's control. The contents of the container are warranted to be free from any other defect for 2 years from the date of manufacture. All warranties and guarantees are limited to refund or replacement of product used with proof of purchase. No other warranty or guarantee is expressed or implied.

Contains a mixture of
5-chloro-2-methyl-4-iso-thiazolin-3-one,
2-methyl-2H-isothiazol-3-one
and 1,2-benzisothiazol-3(2H)-one.
May produce an allergic reaction.

Eu limit value for this product (cat A/g) 30g/l (2010).
This product contains max 30g/l VOC.

Safety data sheets (MSDS) available on request.

BEDEC
THE PAINT COMPANY

Innovators in Water-based Technology

Bedec Products Ltd., Units 1 & 2 Poplars Farm, Aythorpe Roding, Dunmow, Essex. CM6 1RY

Tel: +44 (0) 1279 876 657

Email: info@bedec.co.uk

www.bedec.co.uk